



1/2" 1.2/6mm C			1/3"
FOCAL LENGTH		f=6mm	
MAX. DIAMETER (RATIO)		F=1:1.2~close	
PICTURE SIZE		4.8x6.4mm	3.6x4.8
ANGLE	VER. ANGLE	43.5°	33.2°
	HOR. ANGLE	56.2°	43.5°
	DIA. ANGLE	67.0°	53.2°
DISTORTION (TV)		-0.2%	-0.2%
WORKING DISTANCE	500mm	-0.012x	
	400mm	-0.015x	
	300mm	-0.020x	
	200mm	-0.039x	
	100mm	-0.054x	
MINIMUM FOCUS DISTANCE		0.1m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		9.3mm in air (Mechanical 8.2mm in air)	
FILTER SCREW SIZE		M30.5x0.5	
FRONT/REAR EFFECTIVE DIA.		Front ϕ 21.1mm Rear ϕ 15.4mm	
MOUNT		C-MOUNT	
EXIT PUPIL		-112mm	
TEMPERATURE RANGE		-10~+50° C	
STORNG TEMPERATURE RANGE		-20~+60° C	
RESOLUTION CENTER/CORNER		Center 120lp/mm Corner 100lp/mm	
WEIGHT		100g	

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺 度	1/1	承 認	八木	製 図	富永
		機 種 名	1/2" F1.2/6mm				
		機 種 番	LM6NCM				
2012.06.21	作成年月日						